

CKiX Series

Engineered for 100 Volt transformer isolated systems



Model	Stereo			Bridged 200 Volt	Class	RMS	Maximum
	50 Volt*	70.7 Volt*	100 Volt				
CKi150x	75W	75W	75W	150W	AB	105V	150V
CKi300x	150W	150W	150W	300W	AB	105V	150V
CKi500x	250W	250W	250W	500W	AB	105V	150V
CKi800x	400W	400W	400W	800W	AB	105V	150V

50, 70.7, and 100 Volt power rating is Watts per channel, both channels driven, 40Hz -20kHz, 0.1% THD+N

*50 and 70.7 Volt units are options that must be specified at time of order

Model	1/8 power	1/3 power	Rack U	Weight	Idle (240V)	1/8 Power	1/3 Power	Maximum*
CKi150x	363	427	3	32.00 / 14.55	.25A	.57A	.77A	1.88A
CKi300x	555	1683	3	35.00 / 15.91	.25A	1.6A	2.1A	3.2A
CKi500x	810	1024	3	35.00 / 15.91	.3A	2.2A	3.2A	4.4A
CKi800x	1195	1536	3	57.00 / 25.91	.4A	3.5A	5.2A	7.5A

lbs / kg

*circuit breaker rating, 240 Volt