

CKiS Series

Designed to drive low impedance loads



| Model | Stereo | | | Bridged | | Class | RMS | Maximum |
|------------------|--------|-------|-------|---------|-------|-------|-----|---------|
| | 8 Ω | 4 Ω | 2 Ω | 8 Ω | 4 Ω | | | |
| CKi100s | 60W | 90W | N/A | 180W | N/A | AB | 22V | 31V |
| CKi200s | 120W | 175W | N/A | 350W | N/A | AB | 32V | 45V |
| CKi400s | 255W | 320W | N/A | 510W | N/A | AB | 56V | 64V |
| CKi800s | 440W | 670W | N/A | 880W | N/A | AB | 64V | 90V |
| CKi800-2s | 420W | 670W | 870W | 880W | 1740W | H | 64V | 90V |
| CKi1200s | 630W | 940W | 1130W | 1880W | 2260W | H | 78V | 110V |
| CKi1600s | 815W | 1130W | 1440W | 2260W | 2880W | H | 90V | 127V |

power ratings are Watts per channel, both channels driven, 1kHz, 0.02% THD+N

| Model | 1/8 power | 1/3 power | Rack U | Weight | Idle (120V) | 1/8 Power | 1/3 Power | Maximum* |
|------------------|-----------|-----------|--------|---------------|-------------|-----------|-----------|----------|
| CKi100s | 612 | 780 | 2 | 26.63 / 12.09 | .5A | 1.65A | 2.3A | 3.5A |
| CKi200s | 1100 | 1380 | 2 | 29.44 / 13.37 | .6A | 3.0A | 4.2A | 6.5A |
| CKi400s | 2120 | 2820 | 2 | 30.44 / 13.82 | .7A | 5.8A | 8.6A | 12A |
| CKi800s | 3584 | 4700 | 3 | 50.20 / 22.80 | .7A | 10.0A | 14.8A | 15A |
| CKi800-2s | 1210 | 3600 | 3 | 70.65 / 32.08 | .7A | 4.2A | 12.1A | 20A |
| CKi1200s | 3164 | 5040 | 4 | 70.65 / 32.08 | 1.3A | 9.6A | 17.3A | 26A |
| CKi1600s | 3154 | 6525 | 4 | 70.65 / 32.08 | 1.3A | 10.0A | 22.6A | 30A |

lbs / kg

* circuit breaker rating, 120V / 4 Ω