

CKiV Series

Designed specifically for 70 Volt distributed applications



Model	70.7 Volt	140 Volt*	Class	RMS	Maximum
CKi100v	50W	100W	AB	92V	130V
CKi200v	100W	200W	AB	92V	130V
CKi400v	200W	400W	AB	92V	130V
CKi800v	400W	800W	AB	92V	130V
CKi1600v	800W	1600W	H	92V	130V
CKi2400v	1200W	2400W	H	92V	130V

70.7 Volt power rating is Watts per channel, both channels driven, 20Hz -20kHz, 0.02% THD+N
 *bridged mono operation

Model	1/8 power	1/3 power	Rack U	Weight	Idle (120V)	1/8 Power	1/3 Power	Maximum*
CKi100v	269	304	2	25.26 / 11.47	.5A	.76A	1.02A	2.5A
CKi200v	816	932	2	27.20 / 12.35	.5A	2.2A	2.83A	4.2A
CKi400v	1304	1634	2	30.66 / 13.92	.6A	3.6A	5.1A	7.0A
CKi800v	2540	3263	3	50.20 / 22.80	.8A	7.0A	10.1A	15A
CKi1600v	2600	5000	4	70.65 / 32.08	1.3A	8.0A	17.0A	30A
CKi2400v	3100	6500	4	70.65 / 32.08	1.3A	10.0A	23.0A	30A

lbs / kg

* circuit breaker rating, 120V